PRIDE MOBILITY
LIVE YOUR BEST®

>50 km
Range per Charge

181 kg
Weight Capacity

180.3 cm
Turning Radius



PATHRIDER® 140 XLE

Luxurious Outdoor Comfort and Performance

Packed with high-performance elements such as full suspension, low-profile tyres, and a hydraulic sealed brake system, the Pathrider® 140XLE embodies power and precision. Its sleek design is complemented by luxurious standard features like a wraparound delta tiller, digital display screen, new terrain pneumatic gripping tyres, and LED lighting, making it the ultimate choice for outdoor adventures.



Exclusively distributed by

aidacare™
HEALTHCARE EQUIPMENT

AFY394.2.200524

PATHRIDER® 140 XLE



Emergency hydraulic hand brakes



Digital console screen



Adjustable front and rear suspension

RANGE PER CHARGE (MAX)[1,3]	>50 km
MAXIMUM WEIGHT CAPACITY	181 kg
TURNING RADIUS[2]	180.3 cm
MAXIMUM SPEED[1]	10 km/h
LENGTH & WIDTH[2,5]	L: 142.2 cm W: 69.2 cm
SEAT TYPE DEPTH & WIDTH (STANDARD)	High-back, pillow-top L: 48.3 cm (19") W: 45.7 cm (18")
SEAT-TO-DECK HEIGHT[2]	45.7 cm - 49.5 cm
SEAT-TO-GROUND HEIGHT[2]	56.1 cm - 61.2 cm
GROUND CLEARANCE[2,4]	13.3 cm at rear frame

OVERALL WEIGHT (NOT INC BATTERY)[2,6]	123 kg
WEIGHT OF HEAVIEST PIECE[2]	93 kg (main frame doesn't disassemble)
SUSPENSION	Adjustable front and rear suspension
3W/4W OPTION	4W
FRONT TYRES[2]	13" pneumatic
REAR TYRES[2]	13" pneumatic
BATTERY REQUIREMENTS[8]	2 x 100amp/hr
BATTERY CHARGER	Off-board, 8A
BATTERY WEIGHT[2]	25 kg
COLOUR OPTIONS	Orange - SCT670504 Yellow - SCT670505 Red - SCT670506

1. Varies with user weight, terrain type, battery amp hour (AH), battery charge, battery condition and tyre condition. This specification can be subject to a variance of 10%.
2. Due to manufacturing tolerances and continual product improvement, this specification can be subject to variance of 3%.
3. Tested in accordance with ANSI/RESNA, WC Vol 2, Section 4 and ISO 7176-4 standards. Results derived from the theoretical calculations based on battery specification and drive system performance. Test conducted at maximum weight capacity.
4. Does not account for anti-tip clearance.
5. Width of base (not including seat).
6. Includes standard seat weight.

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tyre pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of 3%. Special order seats or non-standard dimensions will not fold-flat and depth-adjustable.

Exclusively distributed by

aidacare™
HEALTHCARE EQUIPMENT

1300 133 120
www.aidacare.com.au

PRIDE® MOBILITY
LIVE YOUR BEST®

Certified System
Quality
ISO 9001
SAI GLOBAL

AFY394.6 241025